


Biophotonics & Industrial



LaserBoxx

Same package for all colors

Low Noise CW Monolithic DPSS benefits

- Interchangeable controller
- Low profile laser head (32mm)
- Tailored beam diameter capability (0.6 up to 1.4mm)
- Graphic User Interface with remote diagnostics

Laser Diode modules benefits

- Controllers integrated into laser head
- Fast TTL and analog modulation
- Remote *ControlBoxx* with power display (CDRH)
- Optional clean up filter

Common key features

- TEM₀₀ Beam
- Ultra Low Noise < 0.2% rms
- Beam pointing < 5 μm/°C
- USB and RS232 computer interface
- SM/PM/MM fiber coupling options
- Industry standard package (100x40x40 mm)

Super Resolution Imaging
Confocal Microscopy
Flow Cytometry
DNA Sequencing
Optogenetics
Fluorescence Excitation

Polymer Curing
Material Analysis
Laser Marking



375 405 445 473 488 515 532 553 561 594 640 660 705 730 785

Specifications

LBX-375 LBX-405 LBX-445 LBX-473 LBX-488 LBX-515 LBX-532 LMX-532L LMX-553L LMX-561L LBX-561* LBX-594* LBX-638

Optical specifications

Package	LBX-LD							LMX-DPSS			LBX-LD		
Wavelengths	375	405	445	473	488	515	532	532	553	561	561*	594*	638
Wavelength range	± 5							± 1			± 2		+ 5/- 2
Linewidth	< 1.5							< 1			< 1		
Laser type	Laser Diode							DPSS			Doubled LD		

Single Mode (TEM₀₀)

Output Power	20, 70	50, 100 120, 300	100	100	50, 100 150, 200	80	50	100, 150 200, 300	25, 50 100, 200	25, 50, 100 200, 300	40	100, 150	
Power Stability over 8 hours and ±3°C, p-p	± 0.5							± 1			± 0.5		± 0.5
Optical Noise rms, 10Hz - 20MHz	< 0.5							< 0.2			< 0.2		< 0.5
Beam Diameter (typ.) at 1/e ² , at 50mm from aperture	1.3 ²	0.9 or 0.7 ¹	1.0 or 0.7 ¹	1.2 or 0.8 ¹			1.0	0.7			0.7	0.8 ¹	
Beam Divergence (typ.) at 1/e ² , full angle, in far field	0.6 or 1.0 ¹						0.8	1.0			1.0	1.3 ¹	
Beam Circularity in far field	> 90												
Beam Quality (typ.)	< 1.35	< 1.25					< 1.2	< 1.1			< 1.25	< 1.25	
Polarization Ratio Vertical	> 100:1												
Beam Pointing stability	< 5												

PM Fiber Coupling option

Output Power FC/APC connectors, 1.5m fiber length	Call	35, 70 85, 210	70	70	35, 70 100, 140	55	35	70 to 210	17 to 140	17 to 210	28	70, 100

Modulation

Digital Modulation													
Rise / Fall time 10% - 90%	<5 ³		<10					n/a			n/a		< 15
Extinction depth	100							n/a			n/a		100
Analog Modulation													
Bandwidth 3dB cut off frequency	> 0.4	> 1 (APC) / > 4 (ACC)					10 kHz	n/a			1		
Rise / Fall time 10% - 90%	< 700 (APC) / < 150 (ACC)							20 μs	n/a			< 700	
Extinction depth	100							n/a			100		100

¹Beam diameters and divergences for Circular Small Beam (CSB) versions
Dedicated for laser combiner


² Elliptical Beam version available

³ 10 ns Rise/ Fall time for LBX 405-300


DPSS Monolithic Resonator

The unique feature of the LaserBoxx DPSS is a proprietary, alignment-free monolithic resonator. The elements in the cavity are assembled into a single ultra-low-loss optical subsystem, using a proprietary crystal bonding technique.

A highly transparent compound, deposited on chemically activated end-faces of two crystals, creates a bond that is extremely robust over time, temperature variations, and insensitive to mechanical vibrations. Dielectric mirrors coated at the end-faces of the crystals complete the monolithic assembly with no moving parts.




Beam Profile
LBX-488-100-CIR-OE




Beam Profile
LMX-553L-200-COL-PP

Power Stability
LMX-561L Power vs temperature



Relative Intensity Noise
LMX-561L-200



LBX-LD Platform

The LBX-LD line is a performing controller integrated platform for laser diode and 532 nm, 50 mW DPSS modules in 100 x 40 x 40 mm³ industry standard package. The LaserBoxx provides superior beam quality, excellent stability and fast modulation capabilities.

Biophotonics & Industrial

LBX-642	LBX-660	LBX-705	LBX-730	LBX-785	Units
LBX-LD					
642	660	705	730	785	
+3/-5	±5	±10	±5		nm
< 1.2		< 1.2			
Laser Diode					
130	100	30	30	130, 250*	mW
± 0.5					%
< 0.5					%
0.8 ¹		1.2 ¹			mm
1.3 ¹		1.0			mrad
> 90					%
< 1.25					M ²
> 100:1					-
< 5					μrad/°C
90	70	20	20	90, 175*	mW
< 15					ns
100					%
> 1 (APC) / > 4 (ACC)					MHz
< 700 (APC) / < 150 (ACC)					ns
100					%

¹ Preliminary specifications

System Specifications

Package	LMX-DPSS		LBX-LD		Units
	P&P	OEM	P&P	OEM	
Laser Head					
Operating temperature measured at base, non condensing	10 - 45		10 - 50		°C
Start up time	< 10		< 2		min
Heat dissipation	Heatsink provided	< 20	< 10		W
Dimensions (LxWxH)	160 x 40 x 84	100 x 40 x 40 ¹			mm ³
Controller					
Input Voltage	80 - 240 V AC	4 - 5.5 V DC	115 - 230 V AC	5 - 6.5 V DC	V
Input Current	-	< 8	-	< 2.5	A
Power Consumption	< 30	-	< 10	-	W
Dimensions ¹ (LxWxH)	135 x 97 x 70	135 x 97 x 30	See ControlBoxx	Integrated into laser head	mm ³
interfacing	RS232, USB, Analog				


¹ Without heatsink
P&P versions are CDRH compliant

Custom Capabilities


If your particular application requires additional features to take full benefit of the Oxixus laser performance, we would be happy to assist you with the design, development and production of these features.

Here are examples of what we offer :



- o Power adjustment
- o Wavelength selection
- o Custom wavelengths
- o Opto-mechanical Subassemblies including:
 - Wavelengths combiner (LBX-4C)
 - AO modulator and AOTF
 - Specific beam diameter and beam shaping
- o Custom control interface
- o Extended operational temperature range



Analog Modulation
LBX-405-100-CIR
up to 4 MHz




Digital Modulation
LBX-488-100-CIR
Rise / Fall times < 10 ns



Fiber coupling options

Fiber coupling options offer rugged and compact solutions to couple LaserBoxx into Polarization Maintaining, Standard Monomode fiber or MM Fiber.



Specifications		
SM and PM Fiber		MM Fiber (50 μm, 0.22 NA)
> 70 %	Coupling Efficiency	> 80 %
100:1	Polarization Ratio	n/a
FC-APC	Fiber Output Connector	SMA
± 2 %	Power Stability over 8 hours, ± 1.5 °C	± 2 %
1.5 m	Fiber length	1.5 m




VISIBLE AND INVISIBLE LASER RADIATION
AVOID EXPOSURE TO BEAM
CLASS 3B LASER PRODUCT
Power up to 500 mW


VISIBLE AND INVISIBLE LASER RADIATION
AVOID EYE OR SKIN EXPOSURE TO
DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT

Mechanical Drawings

LMX series, PP
DPSS Laser




P&P Controller




CDRH compliant


LMX series, OEM
DPSS Laser




OEM Controller




LBX-LD series, PP




LBX-LD series, OEM



P&P remote ControlBoxx




Rear view



CDRH compliant

LaserBoxx optional heatsink

Optional air-forced heat sink for maximum ambient temperature of 35°C. Including power supply.



Contact us:

Oxxius S.A.
4 rue Louis de Broglie
F-22300 Lannion, France
Phone: +33 296 48 70 28
Fax: +33 296 48 21 90
sales@oxxius.com
www.oxxius.com

USA	RPMC Lasers	rpmc@rpmclasers.com	(+1) 636 272 7227
BeNeLux	Oxxius S.A.	sales@oxxius.com	(+33) 296 48 70 28
France	Opton-Laser International	ventes@optonlaser.com	(+33) 1 69 41 04 05
Germany	Laser 2000 GmbH	contact@laser2000.de	(+49) (0) 8153 4050
Italy	Laserpoint s.r.l	sales@laserpoint.it	(+39) 02 274 00236
Poland	Scitec Instruments Polska	sales@scitecinstruments.pl	(+48) 22 406 8127
Scandinavia	Laser 2000 GmbH	info@laser2000.se	(+46) 8 555 36 235
Spain/Portugal	Laser 2000 SAS	info@laser2000.es	(+34) 650 529 806
Switzerland	Dyneos AG	info@dyneos.ch	(+41) 52 355 1240
UK/Ireland	Laser 2000 Ltd	sales@laser2000.co.uk	(+44) 1933 461666
UK/Ireland	Scitec Instruments Ltd	sales@scitec.uk.com	(+44) 1225 864 200
Israel	Applied Tech. Services (ATS)	dror@ats.co.il	(+972) 09-9574111
China	Aunion Tech Co., Ltd	jinlong.wu@haoliangtech.com	(+86) 21 6257 8098
Japan	Autex, Inc.	sales32@autex-inc.co.jp	(+81) 3 322 66321
Korea	L2K Co., Ltd	sales@l2k.kr	(+82) 42 934 7744
Singapore	Acexon Technologies	lawrence.chua@acexon.com	(+65) 6565 7300
Taiwan	Bio Accord	biotical@ms37.hinet.net	(+886) 2 2250 5019
Australia	Lastek Pty Ltd	alex.stanco@lastek.com.au	(+61) 8 8443 8668