

## Raman fiber probe



product line includes the high sensitivity Raman fiber optic probe to be used with any Raman spectrometer.

Available in two options – multi-wavelength excitation (630-785 nm) and single-wavelength excitation (532 and 785 nm), these fiber probes have a bifurcated design, connecting the probe to both a laser and a spectrometer. Our Raman probe allows to analyze spectra in fingerprint (FP, 800-1800  $\text{cm}^{-1}$ ) and high wavenumber (HWVN, 2800-3800  $\text{cm}^{-1}$ ) spectral ranges using different lasers. Raman fiber optic probes are compatible with process-interfaces to be cleanable and to enable reaction monitoring in lab, pilot plant and run full automated process control.

### Applications:


- ✓ Reaction monitoring in real time
- ✓ Process Analytical Technologies (PAT)
- ✓ Analytical Characterization
- ✓ Biopharmaceutical Analysis
- ✓ Biofuel Development & Production

### Features:

- ✓ On-line Raman spectroscopy
- ✓ Multi-wavelength excitation (630-785 nm)
- ✓ Flexible and robust for industrial applications in harsh environment
- ✓ Compatible with all fiber optic spectrometers

## Specifications:

Excitation Wavelength	630-785 nm "Multi-wavelength excitation" (ideal for use with dual-lasers, e.g., 680 + 785 nm) – Standard. Single-wavelength excitation: 532 and 785 nm Standard. <i>other configurations on request: 405, 473, 488, 514, 532, 633, 670, 780, 785, 830, 1064 nm</i>
Laser Spot at the sample	collimated beam (OD ~ 3 mm) or focused beam (OD ~ 0.2 mm) <i>other configurations on request</i>
Spectral Range Cut-Off	805 nm (300 cm <sup>-1</sup> for 785 nm laser) – for Multi-wavelength 792 nm (100 cm <sup>-1</sup> for 785 nm laser) – for Single-wavelength
Filter Efficiency	Optical Density > 6 for Laser rejection Transmission > 95% for Raman shift
Laser Transmission	> 80%
Fiber type	Laser - NIR105/125 NA=0.22 Detector - NIR200/220 NA=0.22
Window Material	Sapphire AR coated
Lens Material	Fused Silica AR coated
Window Sealing Material	Epoxy glue
Probe Shaft & Body Material	Stainless Steel
Sealing Material	FPM (Viton)
Shaft Size	OD = 12 mm, length = 200±5mm OD = 6 mm, length = 100±5mm
Fiber Length	1.2m + 2 legs of 0.5m each
Total Length (shaft + fiber)	2.00 ± 0.05m
Input / Output Connectors	FC/PC or SMA905
Protection	Liquid Tight Protection (LTP)
Operating Temperatures	from -20°C to 200°C (up to 300°C on request)
Pressure (max)	100 Bar



Aunion Tech Co.,Ltd

Tel: +86-21-51083793; Phone:+86-13162059831

Mail: jun-wang@auniontech.com; www.auniontech.com

3rd Floor, Building 6, 2007 Hongmei Road, Xuhui District, Shanghai 201103 P.R. China