


THz Mirrors

Tydex offers mirrors for applications where THz radiation has to be fully reflected.



The following THz mirrors are available from stock:

No.	Diameter		Thickness
	mm	inches	mm
1	25.4	1.0	6.35
2	38.1	1.5	6.35
3	50.8	2.0	6.35
4	76.2	3.0	6.35

Custom sizes are manufactured upon request. The finished parts of different dimensions are available from stock and supplied within a week. Please check the Optics stock at our website. For price quotation and delivery please fax or e-mail us

Common specification:

Material of substrate	Quartz glass
Type	Plano-plano
Dimensions tolerance, mm	+/-0.25
Clear aperture, %	>=90
Surface quality of polished surfaces, scr/dig	40/20
Surface quality of ground surface, Ra	2.5
Surface accuracy, λ @633nm	1/2
Coating	Protected gold
Thickness of gold layer, nm	~400

Typical reflection curve is shown below. Measurements were made up to 1000 μm . However, operating wavelength range is much wider.




Fig.1 Reflection of THz mirror

Aunion Tech Co.,Ltd

Floor 3, F Building, No. 86 Caobao road, Shanghai 200235 P.R. China

Tel: +86-21-51083793

Fax: +86-21-34241962

上海昊量光电设备有限公司 Phone: 4006-888-532 W-Chat: Auniontech Website: www.auniontech.com E-mail: info@auniontech.com

E-Mail: info@auniontech.com

Website: www.auniontech.com