QTFM Gen-2

The QuSpin Total-Field Magnetometer (QTFM) is a compact, high-sensitivity hybrid scalar + three-axis vector atomic magnetometer for geophysical applications. It is extremely accurate, stable, and can resolve minute field changes. A compact, low-power package makes it ideal for use in a wide range of applications from magnetic observatories to small, mobile platforms such as UAVs.

Release Notes: link

Technical Specifications (Preliminary)

Sensitivity: Scalar: <20pT/√Hz; Vector: <0.1 nT/√Hz (optional

add-on)

Data Rate: 1000 samples/sec (maximum)

Bandwdith: 500 Hz

Deadzone: Axial only, < +/- 7° cone about earth's field (typical

< 5°) (link)

Heading Error: <3 nT uncompensated **Dynamic Range:** 1000 nT to 150,000 nT

Operating Temperature: -15 deg. C to 55 deg. C

Size: 36×17.8×11.6 mm (sensor head), 91x20x14.4 mm

(electronics)

Weight: 15 g (sensor head + electronics)

Power: 5V to 10V input, 2 W total (sensor + electronics), 3W

during startup

Outputs: UART, USB

Max Gradient Field: 300 nT/cm

Calibration: None

Type: Pulsed laser pumped rubidium free induction decay (link)



QUSPIN

QTFM Gen-2 enters a dead zone (non-functional) when the sensor axis points inside $\theta \approx 7$ -degree contabout the background field.

OTFM recovers instantaneously once it is oriented away from the dead zone.

Features

- Optional addon: Integrated, stable, low-noise three-axis vector outputs (synthetic1)
- Flat spectral response (no frequency-dependent response roll-off)
- Built-in customizable digital filters (low-pass, high-pass, notch)
- Multiple sensors can be precisely synchronized for gradiometry
- Negligible dead zones
- No slew rate limitations (can tolerate extremely magnetically noisy environments)
- Built-in high-resolution frequency counter

1Vector outputs are synthetically derived (calculated) from scalar measurements by applying bias fields in interleaved measurement cycles (link)

