



SID4 V VACUUM COMPATIBLE

HIGH RESOLUTION WAVEFRONT SENSOR

PHASICS is innovating by proposing the first off-the-shelf vacuum compatible wavefront sensor on the market.

SID4 V is designed to perform wavefront measurements **under high vacuum**. The wavefront measurement is realized in-situ in the same conditions as the experiment. With PHASICS' unique strategy for **adaptive optics**⁽¹⁾ it is now possible to correct the aberrations of every single optical element up to the target location inside the vacuum chamber.

It is also used to characterize laser beams **after compression** inside the compressor vessel.

Finally, gas jet and plasma density⁽²⁾ are now measured as close to the target as possible.

KEY FEATURES



Large spectral range acceptance



High resolution 416 x 360 phase pixels



Diverging beam compatible



Low outgassing



Operating under vacuum & atmospheric pressure



Compactness



SID4 V VACUUM COMPATIBLE

HIGH RESOLUTION WAVEFRONT SENSOR

ADVANTAGES

- Invariant to thermal and mechanical vacuum constraints
- Tolerates vacuum-cycles without any performance decrease
- MTBF > 10 years

DESIGNED FOR VACUUM DOWN TO 10-6 mbar NO CONTAMINATION IN THE VACUUM CHAMBER

SPECIFICATIO	NS
Vacuum compatibility	>10 ⁻⁶ mbar
Wavelength range	400 - 1100 nm
Aperture dimensions	9.98 x 8.64 mm ²
Maximun NA*	0.2
Spatial resolution	24 µm
Phase and intensity Sampling	416 x 360
Accuracy	20 nm RMS
Resolution (Phase)	< 2 nm RMS
Frame rate	10 fps
Real-time processing frequency	3 Hz (full resolution)
Dimensions	73 x 71 x 90 mm ³
Weight * Optional software module necessary	~450 g



PHASICS S.A.

Bâtiment Mercury I - Espace Technologique Route de l'Orme des Merisiers 91190 Saint-Aubin FRANCE

Tel: +33(0)1 80 75 06 33

PHASICS CORP.

1023 Walnut Street Suite 100 Boulder CO 80302 USA Tel: +1 415 610 9741

one: 4006-888-532 WeCha**www.phasics.com** wyw.a**.contact@phasics.com**auniontech.com